

1.
  - a. i-AUD Script Editor [Delete] OnSelectedCellsDeleted API .
  - b. API .
  - c. [i-AUD] AUD API .
  - 7.0.500.20251217-11 API

**OnSelectedCellsDeleted**

```

OnSelectedCellsDeleted: (
  sender: Grid,
  args: {
    Id: string;
    Cancel: boolean;
    SelectedCells: DataGridCell[];
    SelectedCell: DataGridCell;
  }
) => void
        
```

[Delete] 키를 이용해 그리드의 선택된 셀들의 값을 지울 때 발생합니다.

**Type Declaration**

```

(
  sender: Grid,
  args: {
    Id: string;
    Cancel: boolean;
    SelectedCells: DataGridCell[];
    SelectedCell: DataGridCell;
  }
): void
        
```

**Parameters**

- sender: Grid
- args: {
  - Id: string;
  - Cancel: boolean;
  - SelectedCells: DataGridCell[];
  - SelectedCell: DataGridCell;

Target: Grid

- Id: string  
컨트롤 이름
- Cancel: boolean  
이 값을 true로 설정하시면 선택된 셀들의 데이터 삭제가 취소됩니다.
- SelectedCells: DataGridCell[]  
현재 선택된 셀의 목록
- SelectedCell: DataGridCell  
현재 선택된 셀

Returns void

**Example**

```

Matrix.getObject("DataGrid").OnSelectedCellsDeleted = function(s, e){
  e.Cancel = true;
}
        
```

2.
  - a. i-AUD Designer DataGrid .
  - b. Script Editor OnSelectedCellsDeleted API .

```

DataGrid.OnSelectedCellsDeleted = function(s, e){
  if(e.SelectedCells.length > 0){
    var cell;
    for(var i=0; i < e.SelectedCells.length; i++){
      cell = e.SelectedCells[i];
      if(cell.Value == "DEFAULT") {
        e.Cancel = true; // .
        break;
      }
    }
  }
}
        
```

- ✔
- OnSelectedItemsDeleted , OnDeletingRow .
  - SingleCell (Shift) SelectedItems 0. API GetSelectedCells() .

	<input checked="" type="checkbox"/> API Open	<input type="checkbox"/> UI Open	<input type="checkbox"/> Read Only	<input type="checkbox"/> Not Use	<input type="checkbox"/> Hidden	<input type="checkbox"/> Not Recommend	<input type="checkbox"/>
	<ul style="list-style-type: none"> <li>• i-AUD: 7.3.500.0-202512121512</li> </ul>						